(11)Publication number:

2000-109697

(43)Date of publication of application: 18.04.2000

(51)Int.CL

CO8L 83/10 CO8G 77/442 CO8L101/14 CO9D 7/12 CO9J 11/08 CO9K 3/00

(21)Application number: 10-280946

(22) Date of filing:

02.10.1998

(71)Applicant: NOF CORP

(72)Inventor: TASAKA TOMOHISA

YAMADA TSUNEHISA SUGIURA MOTOYUKI:

(54) WATER-DISPERSIBLE SILICONE COMPOSITION AND SURFACE MODIFIER PREPARED THEREFROM FOR POLYMER MATERIAL

(57)Abstract:

PROBLEM TO BE SOLVED: To obtain a water-dispersible silicone compsn. which exhibits long-lasting mold release properties, abrasion resistance, nonstickiness, water repellency, etc., by incorporating an A-B type block copolymer comprising segment A consisting of a polysiloxane-group-contg. (co)polymer and segment B consisting of a hydrophilic-group-contg. (co)polymer, an org. solvent, and water into the same.

SOLUTION: Segment A is a homopolymer of a polysiloxane-groupcontg. monomer or a copolymer of a polysiloxane-group-contg. monomer and a water- soluble vinyl monomer. The polysiloxanegroup-contg. monomer is represented by formula I or II (wherein R is H or methyl, or R is methyl, ethyl, phenyl or the like, or R is H, phenyl, or the like, or R is methyl, ethyl, hydroxyl, or phenyl; and n is 1-2,000). Segment B is e.g. a homopolymer of a water-soluble vinyl monomer. Pref., the wt. ratio of segment A to segment B in the A-B type block copolymer is (25/75)-(90/10).

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection.